

XPro LITE

Palm-Size Digital Multimeter 

- Data Hold
- Easy-to-Read LCD Display



Overview

The XPro LITE™ Digital Multimeter from XFTP is an ideal tool for electrical maintenance. The multimeter measures AC/DC voltage, DC current, resistance, temperature, transistor and diode values, and electrical continuity. The multimeter features a convenient, large LCD screen and a data hold function. The XPro LITE Digital Multimeter comes complete with a battery, test leads, and a point contact temperature probe.

General Characteristics

Power	9 Volt battery (6F22)
LCD Display Size (H x W)	1.89" x 0.63" (48mm x 16mm)
Weight	0.34 lb (156 g)
Dimensions (H x W x D)	5.12" x 2.91" x 1.38" (130mm x 74mm x 35mm)



SPECIAL FUNCTIONS:

- Diode measurement
- Transistor measurement
- Continuity buzzer
- Data hold
- Backlit display
- Low battery indicator

INCLUDES THE FOLLOWING:

- Test leads
- Battery
- Point contact temperature probe
- Protective sleeve
- User's manual



XFTP by TRILITHIC
9710 Park Davis Drive
Indianapolis, IN 46235

P: 800-344-2412
317-895-3600
F: 317-895-3613
E: xftp@trilithic.com

www.fieldtechproducts.com

Specifications

BASIC FUNCTIONS	RANGE	RESOLUTION	ACCURACY*
DC Voltage	200 mV	100 μ V	$\pm(0.5\% + 2)$
	2 V	1 mV	$\pm(0.5\% + 2)$
	20 V	10 mV	$\pm(0.5\% + 2)$
	200 V	100 mV	$\pm(0.5\% + 2)$
	500 V	1 V	$\pm(0.8\% + 2)$
AC Voltage	200 V	100 mV	$\pm(1.2\% + 10)$
	500 V	1V	$\pm(1.2\% + 10)$
DC Current	2 mA	1 μ A	$\pm(1.0\% + 2)$
	20 mA	10 μ A	$\pm(1.0\% + 2)$
	200 mA	100 μ A	$\pm(1.2\% + 2)$
	10 A	10 mA	$\pm(2.0\% + 5)$
Resistance	200 Ω	0.1 Ω	$\pm(0.8\% + 5)$
	2 K Ω	1 Ω	$\pm(0.8\% + 2)$
	20 K Ω	10 Ω	$\pm(0.8\% + 2)$
	200 K Ω	100 Ω	$\pm(0.8\% + 2)$
	20 M Ω	10 K Ω	$\pm(1.0\% + 5)$
Temperature	-40° to 150° C (-40° to 302° F)	1° C (1° F)	$\pm(1.0\% + 3)$ $\pm(1.0\% + 4)$
	150° to 1000° C (302° to 1832° F)	1° C (1° F)	$\pm(1.5\% + 15)$ $\pm(1.5\% + 15)$

* Accuracy $\pm(\% + \text{minimum resolution digits})$

Input impedance for DC voltage measurement: approximately 10 M Ω